

25 Ani de Buna Practica in MULTImedia&NETworking



SO 1400

Nr.3934

26-6-2015

EXT-TxRx-50





This HDMI Extender includes a transmitter unit (TX) and a receiver unit(RX), working as a pair.

It allows for transmission and extension uncompressed full HD 1080p@60Hz HDMI signal via CAT6/6A/7 network cable, the transmission distance is up to 50 meters with zero latency. This product is perfect for AV transmission in applications of HD conference system, HD video shooting, HD multimedia

education system, home entertainment and signage etc.

FEATURES

Full HD 1080p transmission up to 50m/164ft

- Full compliant with HDMI and HDCP •
 - Compact design with mini size
 - No need of HDMI cable for Plug & Play
 - No software or driver required

SPECIFICATIONS

Items	Specification
Power supply	No power supply attached, use micro usb cable
	to power transmitter
HDMI compliance	HDMI1.3
HDCP compliance	HDCP1.2
HDMI resolution supported	480i@60Hz、480p@60Hz、576i@50Hz、
	576p@50Hz、720p@50/60Hz、
	1080i@50/60Hz、1080p@50/60Hz
Supports audio formats	L/R stereo audio
Maximum transfer rate	10.2Gbps
Audio signal transmission format	L/R stereo audio
Input and output TMDS signal	0.5~1.5Vp-p(TMDS)
Input and output DDC signal	5Vp-p(TTL)
Electrostatic protection of the whole machine	1a Contact discharge level 3
	1b Air discharge level 3
	Standard: IEC61000-4-2
Working temperature	0~50℃
Storage temperature	-10~70℃
Humidity (no condensation)	0~90%
Dimension	71.35(L) x 25.9(W) x 11.05(H)mm
Material	ABS plastics
Color	Black
Weight	TX:10g RX:10g







